

电磁屏蔽直接头

EMC Straight fitting



材质：尼龙 66，黄铜镀镍螺纹

Material: Polyamide 66, Nickel plated brass thread

颜色：黑色 / 灰色

Colour: Black(BL) /Grey(GR)

温度：-45°C~+120°C，短时间 150°C

Temperature range: -45°C ~ +120°C, short-term to 150°C

防护等级：IP66, IP68(与软管及 RLS 密封垫配合使用)

Protection Degree: IP66, IP68(For use with conduits & RLS seal)

特性：高屏蔽和低耦合阻力，能屏蔽电信号和磁场等干扰信号，便于快速安装

Properties: High shielding alternation and low coupling resistance. Disturbance signals such as electrical signals and magnetic fields will be discharged to the housing/casing. Easy and quick installation.



CE UL测试 EN45545

M 螺纹

适配软管尺寸 Fits to Conduit size	型号 Part no.	螺纹 A Thread	B	C	D	E	F	包装(个) Packing
21	RL21-M20-SA-EMV-AD	M20X1.5	14.0	71.4	28.0	11.8	27.0	50
28	RL28-M25-SA-EMV-AD	M25X1.5	16.0	77.0	36.5	16.8	34.0	50
34	RL34-M32-SA-EMV-AD	M32X1.5	16.0	79.3	43.0	21.8	40.0	20
42	RL42-M40-SA-EMV-AD	M40X1.5	16.0	95.0	53.0	30.8	52.0	20
54	RL54-M50-SA-EMV-AD	M50X1.5	16.0	101.5	66.0	42.8	62.0	10
54	RL54-M63-SA-EMV-AD	M63X1.5	16.0	101.5	66.0	42.8	70.0	10

PG 螺纹

适配软管尺寸 Fits to Conduit size	型号 Part no.	螺纹 A Thread	B	C	D	E	F	包装(个) Packing
21	RL21-PG13-SA-EMV-AD	PG13	13.0	70.4	28.0	11.8	27.0	50
21	RL21-PG16-SA-EMV-AD	PG16	13.0	70.4	28.0	11.8	27.0	50
28	RL28-PG21-SA-EMV-AD	PG21	14.0	75.0	36.5	16.8	34.0	20
34	RL34-PG29-SA-EMV-AD	PG29	14.0	77.3	43.0	21.8	40.0	20
42	RL42-PG36-SA-EMV-AD	PG36	17.0	96.0	53.0	30.8	52.0	10
54	RL54-PG48-SA-EMV-AD	PG48	17.0	102.5	66.0	42.8	70.0	10