

黄铜外螺纹直接头

Brass external thread Straight fitting

材质：黄铜镀镍

Material: Nickel-plated brass

温度：-40°C~+125°C

Temperature range: -40°C ~ +125°C

防护等级：IP40-68

Protection Degree: IP40-68

适用软管：SC, SPC, SPLC, SBC, SSC, SPUL, RPC, SSPC

Fitting conduits: SC, SPC, SPLC, SBC, SSC, SPUL, RPC, SSPC



M 螺纹

| 适配软管尺寸 Fits to conduit size | 型号 Part no. | 螺纹 A Thread | B | 尺寸 Dimension(mm) | | | E | 包装(个) Packing |
|-----------------------------------|----------------|-------------------|------|------------------|------|------|----|------------------|
| | | | | C | D | | | |
| 5/16" | SPC12-M16-M | M16X1.5 | 8.5 | 20.0 | 22.0 | 12.0 | 50 | |
| 3/8" | SPC16-M16-M | M16X1.5 | 8.5 | 21.0 | 26.0 | 13.0 | 50 | |
| 3/8" | SPC16-M20-M | M20X1.5 | 8.5 | 21.0 | 26.0 | 13.0 | 50 | |
| 1/2" | SPC20-M20-M | M20X1.5 | 9.0 | 25.0 | 28.0 | 13.0 | 50 | |
| 3/4" | SPC25-M25-M | M25X1.5 | 12.0 | 25.5 | 35.0 | 14.5 | 50 | |
| 1" | SPC32-M32-M | M32X1.5 | 14.0 | 28.5 | 45.0 | 17.0 | 50 | |
| 1 1/4" | SPC40-M40-M | M40X1.5 | 14.0 | 30.5 | 55.0 | 17.0 | 25 | |
| 1 1/2" | SPC45-M50-M | M50X1.5 | - | - | - | - | 20 | |

PG 螺纹

| 适配软管尺寸 Fits to conduit size | 型号 Part no. | 螺纹 A Thread | B | 尺寸 Dimension(mm) | | | E | 包装(个) Packing |
|-----------------------------------|----------------|-------------------|------|------------------|------|------|----|------------------|
| | | | | C | D | | | |
| 5/16" | SPC12-PG9-M | PG9 | - | - | - | - | 50 | |
| 3/8" | SPC16-PG11-M | PG11 | 8.5 | 21.0 | 26.0 | 13.0 | 50 | |
| 3/8" | SPC16-PG13.5-M | PG13.5 | 9.0 | 21.0 | 26.0 | 13.0 | 50 | |
| 1/2" | SPC20-PG16-M | PG16 | 8.0 | 23.0 | 28.0 | 13.0 | 50 | |
| 3/4" | SPC25-PG21-M | PG21 | 12.0 | 25.5 | 35.0 | 14.5 | 50 | |
| 1" | SPC32-PG29-M | PG29 | 14.0 | 30.5 | 45.0 | 16.0 | 50 | |
| 1 1/4" | SPC40-PG36-M | PG36 | 16.0 | 39.0 | 59.0 | 19.0 | 25 | |
| 1 1/2" | SPC45-PG48-M | PG48 | - | - | - | - | 20 | |